
1. Description

- The D1132 is an 8W (P_{SAT}) wideband unmatched gallium nitride (GaN) high electron mobility transistor (HEMT) with first generation RF GaN technology from Raytron.
- The D1132 operates from DC to 8GHz with a 28V supply rail. It is assembled in a lead-free 4.5 x 4.0mm 6-lead DFN plastic package.



D1132-PDS-F01

Figure 1. D1132 Package Outline

2. Applications

- Test and Measurement
- Defense Communications
- Land Mobile Radio
- Wireless Infrastructure

3. Features[1]

- Operating Frequency: DC-8GHz
- Output Power (P_{SAT}): 39.3dBm (9W)
- Linear Gain: 18.6dB
- Typical DE @P_{SAT}: 74.7%
- Operating Voltage: 28V
- CW and Pulse Capable
- Package: DFN 4.50 x 4.00 x 0.75mm

[1] Measured in Raytron DEMO @ 2.6GHz


4. Brief Typical Performance

Table 1. Brief Typical Performance

Parameter	2.6GHz	Units
Linear Gain	18.6	dB
Drain Efficiency	74.7	%
Output Power	39.3	dBm
Output Power	9	W

- Typical Class AB performance in Raytron DEMO, test condition: V_{DS} = 28V, I_{DS} = 100mA, V_{GS} = -2.1V
- Test Condition: Pulse, Pulse width = 100μs, Duty cycle = 10%

5. Block Diagram



D1132-PDS-F02

Figure 2. D1132 Block Diagram

Table of Contents

No.	Contents	Page
1	Description	1
2	Applications	1
3	Features	1
4	Brief Typical Performance	1
5	Block Diagram	1
6	Absolute Maximum Ratings	3
7	Recommended Operating Conditions	3
8	Electrical Characteristics	3
9	Typical Performance	4
10	Wide-band Application Performance (CW)	5
11	Package Outline	6
12	Application Circuit	7
13	DEMO Summary	8
14	Recommended Solder Temperature Profile	9
15	Handling Precautions	9
16	Contact Information	9
17	Disclaimer	10

6. Absolute Maximum Ratings

Table 2. Absolute Maximum Ratings

Parameter	Symbol	Rating	Units
Drain-Source Voltage	V_{DSS}	150	V
Gate-Source Voltage	V_{GS}	-10 ~ +1	V
Operating Voltage	V_{DS}	10 ~ +55	V
Maximum Forward Gate Current	I_{GMax}	1.4	mA
Storage Temperature Range	T_{STG}	- 65 ~ +150	°C
Operating Junction Temperature	T_J	225	°C

7. Recommended Operating Conditions

Table 3. Recommended Operating Conditions

Parameter	Min.	Typ.	Max.	Units
Drain-Source Voltage Range, V_{DS}	-	28	48	V
Drain Bias Current, I_{DS}	-	100	-	mA
Gate-Source Voltage, V_{GS}	-	-2.1	-	V
Channel Temperature, T_{CH}	-	-	225	°C

8. Electrical Characteristics (T_C = 25˚C)

Table 4. DC Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Units
Drain-Source Breakdown Voltage[1] (V_{GS} = -10V, I_{DS} = 1.4mA)	$V_{DS(BR)}$	150	-	-	V
Saturated Drain Current[2] (V_{DS} = 10V, V_{GS} = 1.0V)	I_{Max}	-	1.25	-	A
Gate Threshold Voltage[3] (V_{DS} = 28V, I_{DS} = 1.4mA)	$V_{GS(TH)}$	-3.00	-2.50	-2.00	V
Gate Quiescent Voltage (V_{DS} = 28V, I_{DS} = 100mA)	$V_{GS(Q)}$	-	-2.10	-	V

1. Measured on wafer prior to packaging
2. Measured with packaged device
3. Typical Class AB performance in Raytron DEMO

Table 5. RF Characteristics[1]

Test Method	Parameter	Symbol	Min.	Typ.	Max.	Units
DEMO[2] @2.6GHz	Linear Gain	G_{LIN}	-	18.6	-	dB
	Drain Efficiency	η_D	-	74.7	-	%
	Output Power	P_{SAT}	-	39.3	-	dBm

1. Test Condition: Pulse, Pulse width = 100μs, Duty cycle = 10%
2. Typical Class AB performance in Raytron DEMO, test condition: V_{DS} = 28V, I_{DS} = 100mA, V_{GS} = -2.1V

Table 6. Dynamic Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Units
Input Capacitance	C_{GS}	-	1.97	-	pF
Output Capacitance	C_{DS}	-	1.01	-	pF
Feedback Capacitance	C_{GD}	-	0.19	-	pF

- Test Condition: V_{DS} = 28V, V_{GS} = -8V, f = 1MHz

9. Typical Performance




Figure 3. 2.6GHz Gain and DE @ MXP vs. Output Power




Figure 4. 2.6GHz Gain and DE @ MXE vs. Output Power

- Typical Class AB performance in Raytron DEMO, test condition: V_{DS} = 28V, I_{DS} = 100mA, V_{GS} = -2.1V
- Test Condition: Pulse, Pulse width = 100μs, Duty cycle = 10%

10. Wide-band Application Performance (CW)

Table 7. RF Characteristics (CW)

Parameter	5.7GHz	5.8GHz	5.9GHz	Units
Linear Gain	11.7	12.6	12.3	dB
Power Gain	8.7	9.6	9.3	dB
Drain Efficiency	63.8	59.6	59.5	%
Output Power	38.5	38.1	37.9	dBm
Output Power	7	6	6	W

- Typical Class AB performance in Raytron DEMO_G, test condition: V_{DS} = 28V, I_{DS} = 100mA, V_{GS} = -2.1V
- Test Condition: CW




Figure 5. Gain and DE vs. Output Power (5.7GHz-5.9GHz)




Figure 6. Gain and DE vs. Freq. (5.7GHz-5.9GHz)

- Typical Class AB performance in Raytron DEMO_G, test condition: V_{DS} = 28V, I_{DS} = 100mA, V_{GS} = -2.1V
- Test Condition: CW
- The output power reaches 37.9dBm(6W) at 5.7-5.9GHz when V_{DS} = 28V.

11. Package Outline

■ Pin Layout




Figure 7. D1132 Pin Layout

Table 8. Pin Description

Pin	Symbol	Description
1/3/4/6	NC[1]	Not Connected
2	RF_{IN} / V_G	RF Input / Gate Voltage
5	RF_{OUT} / V_D	RF Output / Drain Voltage
7	Exposed PAD[2]	Ground / Source

[1] All no connection pins may be left floating or connected to the ground.

[2] The exposed pad centered on the package bottom must be connected to RF and DC ground. This path must also provide a low thermal resistance heat path.

■ Mechanical Drawing (Package Type: DFN 4.50 x 4.00 x 0.75mm)




Figure 8. D1132 Mechanical Drawing

12. Application Circuit

■ Schematic




Figure 9. D1132 DEMO_G Application Circuit Schematic

Table 9. Bias Procedure

Bias-up Procedure	Bias-down Procedure
1) Set V_{GS} to the pinch-off voltage, typically -6V	1) Turn off RF signal
2) Turn on V_{DS} to nominal supply voltage (28V)	2) Turn off V_{DS}
3) Slowly adjust V_{GS} until I_{DS} current is attained	3) Wait two seconds to allow drain capacitor to discharge
4) Apply RF input power to desired level	4) Turn off V_{GS}

■ Layout




Figure 10. D1132 Application Circuit Layout (5.7-5.9GHz)
（DEMO_G Size: 4.0 x 3.5cm）

Table 10. Bill of Materials

Component	Value	Description	Manufacturer	Part Number
PCB	20mil	N/A	Rogers	RO4350B
C1	2.0pF	C0G 250V 0603 Capacitor	Murata	GQM1875C2E2R0BB12
C2	1000.0pF	C0G 250V 0603 Capacitor	Murata	GCM1885C2A102JA16D
C3	1.0uF	X7R 100V 1210 Capacitor	Murata	GRM32ER72A105KA01
C4	0.9pF	C0G 250V 0805 Capacitor	Murata	GQM2195C2ER90WB12
C5	0.7pF	C0G 250V 0805 Capacitor	Murata	GQM2195C2ER70WB12
R1	10.0Ω	1/10W 0603 Resistor	Yageo	AC0603FR-0710RL

13. DEMO Summary

Table 11. DEMO Summary

No.	D1132 DEMO Name	V_{DS} (V)	Freq (GHz)	Linear Gain(dB)	P_{SAT} (dBm)	P_{SAT} (W)	Drain Efficiency (%)	Pulse or CW
1	DEMO_A, 7W	28	2.4-2.5	17.8	38.3	7	67.1%	CW
2	DEMO_B, 7W	28	2.5-5.2	12.0	38.5	7	52.0%	CW
3	DEMO_C, 5W	28	2.5-6.4	10.0	37.3	5	35.9%	CW
4	DEMO_D, 6W	28	4.3-4.5	19.0	37.9	6	59.2%	CW
5	DEMO_E, 5W	28	4.6-6.4	8.4	37.2	5	46.0%	CW
6	DEMO_F, 8W	32	5.1-5.9	10.1	39.2	8	45.8%	CW
7	DEMO_G, 6W	28	5.7-5.9	11.7	37.9	6	59.5%	CW
8	DEMO_H, 5W	28	6-7.2	11.2	37.0	5	44.0%	CW
9	DEMO_I, 5W	28	6-7.5	10.0	36.5	5	37.6%	CW

14. Recommended Solder Temperature Profile




Figure 11. Recommended Solder Temperature Profile

15. Handling Precautions

- **ESD Caution**

  ESD (electrostatic discharge) sensitive device. Charged devices and circuit boards can discharge without detection. Although this product features patented or proprietary protection circuitry, damage may occur on devices subjected to high energy ESD. Therefore proper ESD precautions should be taken to avoid performance degradation or loss of functionality.



16. Contact Information

For the latest specifications, additional product information, technical support and sales support, please contact:

- **Email:** RF.support@raytrontek.com
- **Web:** www.raytrontek.com

17. Disclaimer

The information provided here is believed to be reliable at the time of publication. Raytron reserves the right to make changes to its products, specifications and product descriptions at any time without notice. Raytron assumes no responsibility for the use of this information and all such information should entirely be at the user's own risk. Raytron makes no warranty about the suitability of its products for specific purpose or application and disclaims all liability, including without limitation consequential and incidental damages. Raytron does not authorize or warrant any Raytron products for use in the life support devices or systems.

Raytron Microwave
Copyright @ Raytron Technology Co.,Ltd